

Power Supply

DIN 9/200

input	230V AC
output	9V DC
maximal output current	200mA
no-load voltage	18 V
output voltage at 50% load (100mA)	13,3 V
output voltage at 100% load (200mA)	10,1 V
input connector	screw
output connector	screw
fuse output	T 500mA
optical indication	PWR
mechanical construction	DIN rail 35mm mounting
dimension	90 x 36 x 58mm

DIN 12/600

input	230V AC
output	12V DC
maximal output current	600mA
no-load voltage	12,8 V
output voltage at 50% load (300mA)	10,7 V
output voltage at 100% load (600mA)	9,1 V
input connector	screw
output connector	screw
fuse output	T 1,6A
optical indication	PWR
mechanical construction	DIN rail 35mm mounting
dimension	90 x 52 x 58mm

DIN 48/12

input	36V - 72V DC (option 12 - 36V DC)
output - constant voltage	12V DC
maximal output power	15W
isolation	1 kV
input connector	screw
output connector	screw
fuse input	T 800mA
optical indication	PWR
mechanical construction	DIN rail 35mm mounting
dimension	90 x 52 x 58mm

ZN 9/300

input	230V AC
output	9V DC
maximal output current	300mA
no-load voltage	13,7 V
output voltage at 50% load (150mA)	10,9 V
output voltage at 100% load (300mA)	9,2 V
output connector	plug 1.3mm
optical indication	PWR
dimension	90 x 80 x 58mm

ZS 9/300

constant voltage

input	230V AC
output	9V DC
maximal output current	300mA
output connector	plug 1.3mm
optical indication	PWR
dimension	90 x 80 x 58mm

ZN 12/300

input	230V AC
output	12V DC
maximal output current	300mA
no-load voltage	19,8 V
output voltage at 50% load (150mA)	15,7 V
output voltage at 100% load (300mA)	12,8 V
output connector	plug 1.3mm
optical indication	PWR
dimension	90 x 80 x 58mm

ZS 12/300

constant voltage

input	230V AC
output	12V DC
maximal output current	300mA
output connector	plug 1.3mm
optical indication	PWR
dimension	90 x 80 x 58mm

ZN 12/500

input	230V AC
output	12V DC
maximal output current	500mA
no-load voltage	16,6 V
output voltage at 50% load (250mA)	13,6 V
output voltage at 100% load (500mA)	11,4 V
output connector	plug 1.3mm
optical indication	PWR
dimension	90 x 80 x 58mm

ZS 12/500
constant voltage

input	230V AC
output	12V DC
maximal output current	500mA
output connector	plug 1.3mm
optical indication	PWR
dimension	90 x 80 x 58mm

ZN 12/1600

input	230V AC
output	12V DC
maximal output current	1 600mA
no-load voltage	16,3 V
output voltage at 50% load (800mA)	14,3 V
output voltage at 100% load (1600mA)	12,9 V
output connector	plug 3.6mm
optical indication	PWR
dimension	150 x 80 x 70mm