


## INDUSTRIAL CELLULAR MODEMS AND ROUTERS

### Universal Wireless Ethernet Made Easy



### OVERVIEW

The BT-6000 series cellular modems offer high-speed, secure internet connectivity over the cellular network to m2m applications for real-time remote access, monitoring and control of remote devices. These ruggedized industrial gateways provide truly open wireless TCP/IP connectivity to remote devices and business assets located almost anywhere.



### BENEFITS

- Provides industry standard internet TCP/IP access to remote devices
- Provides real-time readings for better usage and billing management
- Optimizes the use of business assets
- Reduces visits to remote locations resulting in lower employee resources
- Connect multiple devices to a single WAN pipe
- Ideal for hazardous environments (Class 1 Div. 2)
- Certified to work on ALL major North-American cellular carriers
- Compared to traditional wire line:
  - Simpler installation, lower startup costs and faster deployments
  - Lower monthly charges (paid based on data usage)
  - Larger geographical coverage
  - Universal TCP/IP connectivity
- Compared to spread spectrum or licensed radio:
  - Lightning fast – up to 7.2 Mps
  - Open, universal TCP/IP connectivity
  - No site surveys or networks to maintain
  - A better path to future requirements

### FEATURES

- Ultra-reliable, always-on cellular link
- Rugged and compact design
- Multiple interfaces: Ethernet, USB, Serial
- 5 Ethernet ports on the BT-6x21 routers
  - Connect up to 5 Ethernet devices and share the same cellular pipe.
- Remote diagnostics, configuration and updates
  - Eliminates on-site visits to troubleshoot or perform changes on the deployed units.
- IPSEC secure VPN tunneling
  - The ultimate method to block unauthorized access and encrypt the data stream.
- Access Control List
  - Protects access to the modem and host equipment from the internet by only allowing requests from known IP addresses to go through, and blocking all others.
- DHCP server
- Serial IP server with Modbus and DNP3 support
  - Provides internet connectivity to legacy automation equipment by encapsulating the serial port traffic in TCP/IP or UDP/IP packets.
- Power over Ethernet (PoE) optional
  - With a single wire for both data and power, installation is greatly simplified. PoE also allows installing the modem up to 300 feet away from the equipment for an optimal cellular antenna/coverage setup.

## BT-6000 Series Typical Applications

- Meter reading and utility monitoring systems
- RTU/PLC/SCADA for data collection, monitoring and control
- Traffic control and monitoring
- Surveillance and alarm panels
- POS, ATM, Kiosk
- Process Automation (water treatment, Oil and Gas, ...)



## Selection Matrix

Three cellular technologies:

BT-66xx EVDO (3G)	BT-68xx HSPA (3G)	BT-64xx EDGE (2G)
CDMA2000 EVDO Rev. A	GSM WCDMA/HSDPA/HSUPA	GSM EDGE
Backward compatible to 1xRTT	Backward compatible to GPRS/EDGE	Backward compatible to GPRS
800/1900 MHz	800/850/1800/1900/2100 MHz	850/900/1800/1900 MHz
Theoretical speed: 3.1 Mbps	Theoretical speed: 7.2 Mbps	Theoretical speed: 384 Kbps
Typical speed: 1.5 Mbps	Typical speed: 2.2 Mbps	Typical speed: 120 Kbps

Model	Cellular Technology	Ethernet	RS-232	USB	PoE
BT-6401	EDGE	1	1	1	-
BT-6401EB	EDGE	1	1	1	1
BT-6421	EDGE	5	1	1	-
BT-6601-xx*	EVDO	1	1	1	-
BT-6601EB-xx*	EVDO	1	1	1	1
BT-6621-xx*	EVDO	5	1	1	-
BT-6801	HSPA	1	1	1	-
BT-6801EB	HSPA	1	1	1	1
BT-6821	HSPA	5	1	1	-

\* "xx" is the EVDO (CDMA) cellular provider: VZ (Verizon), SP (Sprint) and AL (Alltel) in the U.S. BM (Bell Mobility), TE (Telus Mobility), ST (Sasktel Mobility) and MT (MTS Allstream) in Canada Cellular provider for HSPA is AT&T

Three hardware options:


- Standard modem
- Power over Ethernet
- 5-port Ethernet switch



BT-6401 or BT-6401EB with PoE



BT-6421



BT-6600 and BT-6800



BT-6601 or BT-6601EB with PoE



BT-6801 or BT-6801EB with PoE



BT-6621 or BT-6821



## Specifications

<b>Ethernet Interface</b>	1x RJ45 Ethernet 10/100 auto-sensing (BT-6x00, BT6x01, BT-6x01EB) 5x RJ45 Ethernet 10/100 auto-sensing (BT-6x21)
<b>Serial Interface</b>	1x RS-232 Serial DB9 with rates up to 115200bps
<b>USB Interface</b>	1x USB2.0 mini device port
<b>LED Status Indicators</b>	Power, WAN, Signal, RS232, Ethernet Link & Activity
<b>Inputs &amp; Outputs</b>	1x Reset Button, 1x Digital Output, 1x Digital Input
<b>Dimensions</b>	BT-6x0x: Steel 120 x 96 x 32 mm (4.7" x 3.77" x 1.25"), 453g (1 lb) BT-6x21: Steel 120 x 96 x 51 mm (4.7" x 3.77" x 2.0"), 500g (1.1 lbs)
<b>Power Input</b>	8 - 30 Vdc (12Vdc nominal), Power over Ethernet on "EB" models
<b>Environmental</b>	Operating Temp: -40 to +75°C (-40 to 167°F) Shock: IEC68-2-27, Vibration: IEC68-2-6 Humidity: 5 to 95% non-condensing
<b>Certification</b>	EMC- FCC, part 15 and Industry Canada, ICES-003 Hazardous Locations - Class I, Div. 2, Groups A,B,C,D, UL1604 Electrical Safety - UL508/CSA22.2/14 (CUL)

## Typical Power Consumption in mA at 24 VDC

	BT-660x	BT-6621	BT-680x	BT-6821	BT-6401	BT-6421
<b>Standby</b>	58	125	58	125	58	115
<b>Transmitting</b>	106	175	160	225	123	180
<b>Peaks</b>	222	290	400	470	208	265

**Sixnet** 331 Ushers Road • Ballston Lake, NY 12019 • USA  
+1.518.877.5173 • Fax: +1.518.877.8346 • sales@sixnet.com

SOLUTIONS FOR YOUR INDUSTRIAL NETWORKING CHALLENGES

WWW.SIXNET.COM