

EX-9842

232/485*2

Sound,DOC SSD socket RS-

[Click for larger photo](#)**Key Specifications/Special Features:**

- RS-232x2 for 3rd/4th COM(optional RS-232*1+RS-422/RS-485*1): SMC 665 I/O chip support 2 ports 16-byte FIFO 16C550 high speed RS-232C
- ESS ES1869A 3D high-performance,Mixed-signal, 16-bit stereo chip
- High-quality 20-voice ESFM music Synthesizer, support FM music synthesis In OPL-3 mode
- Programmable sample rates from 4KHz to 48KHz for record and playback
- Full-duplex operation for simultaneous Record and playback
- 3-button hardware master volume control and PC speaker volume control
- Software address mapping, 4DMA and 6 IRQ selections for Plug and Play
- MPU-401 (UART mode) interface for wavetable synthesizers and MIDI devices
- High speed 16-bit ADC and DAC with filters
- 7-channel stereo audio mixer with multi Input Sources (DAC synthesizer, mono in, Microphone in, line in and CD in)
- Output: speaker out, line out and game port
- Supports PC games and applications for SoundBlaster and SoundBlaster Pro,Windows Sound System
- DOC SSD socket: 32-pin socket for M-System DOC SSD 2~144MB

Main Export Markets:

- Worldwide